

# BROCADE OPTICS FAMILY



## ENTERPRISE LAN SWITCHING

## Highly Reliable, Brocade Qualified Optics

### HIGHLIGHTS

- Rigorously tested for performance and reliability by Brocade
- Hot-swappable flexibility in the field for greater ease and lower total cost of ownership
- Standards-based—802.3z, 802.3ah, 802.3u, 802.3ae, and 802.3ak—and compliant as required
- Compliant with Requirements to Reduce Hazardous Substances (RoHS), meeting either RoHS 5 or RoHS 6 EU standards

Brocade® offers a unique set of high-performance, reliable, and cost-effective optical transceivers that help enterprises and service providers meet the challenges of diverse network topologies. To ensure maximum quality, Brocade selects and tests the most reliable, highest-performing optical transceivers on the market, and then warrants their availability, capacity, and performance in Brocade products.

Extensive performance and reliability testing reflects an ongoing commitment to quality. Brocade tests transceivers using the industry's most advanced tools

and instruments to help ensure that they provide the right mix of functionality and performance when used in conjunction with Brocade products. The speed, capacity, reliability, and low cost of ownership that Brocade is known for is also provided in all optical components.

By using Brocade qualified components, organizations can be assured that their warranty and service requirements will be met and that their Brocade products will continually provide the uptime, performance, and reliability required by today's leading enterprise service providers.

## OPTICS FAMILY FEATURES

### 100 MbE Optics

- 100 MbE transceivers support link lengths from 2 km to 40 km
- Both SMF and MMF fiber types
- RoHS 5 and 6 compliant
- Enterprise switching and routing

### 1 GbE Optics

- 1 GbE transceivers support link lengths from 300 m to 100 km
- Both SMF and MMF fiber types
- Coarse Wavelength Division Multiplexing (CWDM) support for distances of 80 km to 100 km
- Core routers
- Security applications

### 10 GbE XFP Optics

- 10 GbE transmissions support link lengths of 26 m to 80 km
- Protocol independent
- Less than one-third the power and size of MSA optic
- Hot swappable
- Digital Optical Monitoring support
- Application delivery and acceleration
- High-Performance Computing (HPC) interconnects
- Service provider traffic management

### POS Pluggable OC12, OC48, and OC192 XFP Optics

- Pluggable XFP Optic
- Ranges from 500 m to 80 km

## PRODUCT SUPPORT FOR FAST ETHERNET

Fast Ethernet Optics	FastIron® Series		FastIron X Series		BigIron® Series	NetIron® Series		
	FLS/FGS/FWS	FCX	FESX	SX	RX	XMR/MLX	M2404	CES
E1MG-100FX-OM	•	•	• <sup>1</sup>	• <sup>2</sup>	•	•	•	•
E1MG-100FX-IR-OM	•	•	• <sup>1</sup>	• <sup>2</sup>	Software v2.6.0	Software v3.9.0		•
E1MG-100FX-LR-OM	•	•	• <sup>1</sup>	• <sup>2</sup>	Software v2.6.0	Software v3.9.0		•

<sup>1</sup> Available only with FESX424HF.

<sup>2</sup> Available only with SX-FI424HF.

## PRODUCT SUPPORT FOR 1 GIGABIT ETHERNET

	Edgelron Series		FastIron Series				FastIron X Series	BigIron Series	NetIron Series			ServerIron Series	TurboIron
	CF	G	FES	FLS/FGS	FCX	FWS	FESX/SX	RX	XMR/MLX/M2404	CES	CER	ADX	TI24X
1 GbE Fiber Optics													
E1MG-SX-OM	•	•	•	•	•	•	•	•	•	•	•	•	•
E1MG-LX-OM	•	•	•	•	•	•	•	•	•	•	•	•	•
E1MG-LHA-OM	•	•	•	•	•	•	•	•	•	•	•		•
E1MG-LHB	•	•	•	•		•	•	•	•	•			
E1MG-BXD			•	•	•		•	•	•	•			•
E1MG-BXU			•	•	•		•	•	•	•			•
E1MG-CWDM80-XXXX		•	•	•		•	•	•	•	•			
E1MG-TX				•	•	•	•	•	•	• <sup>1</sup>	• <sup>1</sup>	•	•

<sup>1</sup> Qualified for 10/100/1000 Mbps speed.

## PRODUCT SUPPORT FOR POS OPTICS

### NetIron Series XMR/MLX

OC12-SFP-MM	•
OC12-SFP-IR1	•
OC12-SFP-LR1	•
OC12-SFP-LR2	•
OC48-SFP-SR1	•
OC48-SFP-IR1	•
OC48-SFP-LR1	•
OC48-SFP-LR2	•
OC192-XFP-SR1	•
OC192-XFP-IR2	•
OC192-XFP-LR2	•

## PRODUCT SUPPORT FOR 10 GIGABIT ETHERNET

	FastIron Series			FastIron X Series		BigIron Series	NetIron Series		ServerIron Series	TurboIron
	FLS	FGS	FCX	FESX	SX	RX	XMR/MLX	CER/CES	ADX	TI24X
10 GbE Fiber Optics										
10G-XFP-SR, LR	•	•	•	•	• <sup>1</sup>	• <sup>2</sup>	• <sup>2</sup>	•	•	
10G-XFP-ER	•	•	•	•	• <sup>1</sup>	• <sup>2</sup>	• <sup>2</sup>	•		
10G-XFP-ZR	•	•	•	•	• <sup>1</sup>	• <sup>2</sup>	• <sup>2</sup>	•		
10G-XFP-ZRD	•	•	•	•	• <sup>1</sup>	• <sup>2</sup>	• <sup>2</sup>	•		
10G-XFP-CX4	•	• <sup>3</sup>		•	•	•	•	•		
10G-SFPP-SR, LR			•			•	•			•
10G-SFPP-LRM										•
10G-SFPP-TWX-XXXX			•				•			•

<sup>1</sup> SX-FI42XGW module supports WAN mode.

<sup>2</sup> All NetIron XMR and BigIron RX 10 GbE modules support WAN mode.

<sup>3</sup> Applicable to FGS624XGP-POE in port 0/3/1 only.

## KEY STANDARDS AND FEATURES

	IEEE Standards	Domestic Safety Standards	International Safety Standards	Wavelength (nm)	Fiber Type	Maximum Cable Distance	Digital Optical Monitoring
<b>Fast Ethernet</b>							
E1MG-100FX-OM	802.3u	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	1310	MMF	2 km	Yes
E1MG-100FX-IR-OM	802.3			1310	SMF	15 km	Yes
E1MG-100FX-LR-OM	802.3			1310	SMF	40 km	Yes
<b>1 GbE Fiber</b>							
E1MG-SX-OM	802.3z	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	MMF	220 m-550 m	Yes
E1MG-LX-OM	802.3z			1310	MMF/SMF	550 m-10 km	Yes
E1MG-LHA-OM	802.3z			1550	SMF	70 km	Yes
E1MG-LHB	802.3z			1550		150 km w/0.18 dB/km cable, 91 km w/standard 0.3 dB/km cable	No
E1MG-BXD	802.3ah			TX:1490, RX:1310		10 km	Yes
E1MG-BXU	802.3ah			TX:1310, RX:1490		10 km	Yes
E1MG-CWDM80-XXXX	802.3z			1470-1610		80 km	No
<b>1000BaseTCopper</b>							
E1MG-TX	802.3z	CSA 60950-1-03/UL	EN 60950-1	N/A	Cat5	100 m	N/A
<b>10 GbE Fiber</b>							
10G-XFP-SR	802.3ae	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	MMF	26 m-300 m	Yes
10G-XFP-LR	802.3ae			1310	SMF	10 km	
10G-XFP-ER	802.3ae			1550		40 km	
10G-XFP-ZR	802.3ae			1550		80 km	
10G-XFP-ZRD	802.3ae			1528.77- 1561.42		80 km	
10G-SFP-SR	802.3ae			850	MMF	300 m	
10G-SFP-LR	802.3ae			1310	SMF	10 km	
10G-SFP-LRM	802.3ae			1310	MMF	220 m	
<b>10GBase Copper</b>							
10G-XFP-CX4	802.3ak	CX4-grade copper cable with CX4 connector, n/a				15 m	No
10G-SFP-TWX-XXXX	802.3ae	Direct attach SFP+ Twinax copper cables				1 m, 3 m, 5 m	Yes

## ORDERING INFORMATION

Part Number	Description
<b>100 MbE SFP Transceivers</b>	
E1MG-100FX-OM	100Base-FX SFP optic MMF, LC connector, optical monitoring capable.
E1MG-100FX-IR-OM	100BaseFX-IR SFP optic for SMF with LC connector, optical monitoring capable. For distances up to 15 km.
E1MG-100FX-LR-OM	100BaseFX-LR SFP optic for SMF with LC connector, optical monitoring capable. For distances up to 40 km.
<b>1 GbE Optics</b>	
E1MG-BXD	1000Base-BXD SFP optic, SMF, 1490 nm, LC connector. This optic can be connected only to an E1MG-BXU at the far end.
E1MG-BXU	1000Base-BXU SFP optic, SMF, 1310 nm, LC connector. This optic can be connected only to an E1MG-BXD at the far end.
E1MG-CWDM80-XXXX	CWDM SFP optic, 80 km, 1470-1610 (total of eight wavelengths supplied by eight optics, each 20 nm apart in wavelength), LC connector.
E1MG-LHA-OM	1000BaseLHA SFP optic SMF, LC connector, optical monitoring capable. For distances up to 70 km.
E1MG-LHB	1000Base-LHB SFP optic, SMF, LC connector, 150 km maximum reach.
E1MG-LX-OM	1000Base-LX SFP optic SMF, LC connector, optical monitoring capable. For distances up to 10 km.
E1MG-SX-OM	1000Base-SX SFP optic, MMF, LC connector, optical monitoring capable.
E1MG-TX	1000Base-TX SFP copper, RJ-45 connector.
<b>10 GbE-XFP</b>	
10G-XFP-SR	850 nm serial pluggable XFP optic (LC), target range 300 m over MMF.
10G-XFP-LR	1310 nm serial pluggable XFP optic (LC) for up to 10 km over SMF.
10G-XFP-ER	1550 nm serial pluggable XFP optic (LC) for up to 40 km over SMF.
10G-XFP-ZR	1550 nm serial pluggable XFP optic (LC) for up to 80 km over SMF.
10G-XFP-ZRD-XXXX-AA	10GBase-ZR DWDM, XFP optic, 80 km, 1528.77 to 1561.42 (total of 41 wavelengths supplied by 41 optics, each 100 GHz apart in frequency).
10G-XFP-CX4	10GBase-CX4, XFP module, 15 m, CX4 connector.
<b>10 GbE-SFP+</b>	
10G-SFPP-SR	10GBASE-SR, SFP+ optic (LC), target range 300 m over MMF.
10G-SFPP-LR	10GBASE-LR, SFP+ optic (LC), for up to 10 km over SMF.
10G-SFPP-LRM	10GBASE-LRM, SFP+ optic (LC), 220 m over OM1/OM2/OM3 MMF.
10G-SFPP-TWX-XXXX	10 GbE SFP+ direct attached copper cable, 1 m, 3 m, or 5 m.

OC12-POS-SFP	
OC12-SFP-MM	POS OC-12 (STM-4) pluggable SFP optic (LC connector). Range up to 500 m over MMF.
OC12-SFP-IR1	POS OC-12 (STM-4) SR-1/IR-1 pluggable SFP optic (LC connector). Range up to 15 km over SMF. No attenuator needed for SR-1 applications
OC12-SFP-LR1	POS OC-12 (STM-4) LR-1 pluggable SFP optic (LC connector). Range up to 40 km over SMF.
OC12-SFP-LR2	POS OC-12 (STM-4) LR-2 pluggable SFP optic (LC connector). Range up to 80 km over SMF.
OC48-POS-SFP 2.5 Gbps	
OC48-SFP-SR1	POS OC-48 (STM-16) SR-1 pluggable SFP optic (LC connector). Range up to 2 km over SMF.
OC48-SFP-IR1	POS OC-48 (STM-16) LR-1 pluggable SFP optic (LC connector). Range up to 15 km over SMF.
OC48-SFP-LR1	POS OC-48 (STM-16) LR-2 pluggable SFP optic (LC connector). Range up to 40 km over SMF.
OC48-SFP-LR2	POS OC-48 (STM-16) LR-2 pluggable SFP optic (LC connector). Range up to 80 km over SMF.
OC192-POS-XFP	
OC192-XFP-SR1 POS	OC-192 (STM-64) SR-1 pluggable XFP optic (LC connector). Range up to 2 km over SMF.
OC192-XFP-IR2	POS OC-192 (STM-64) IR-2 pluggable XFP optic (LC connector). Range up to 40 km over SMF.
OC192-XFP-LR2	POS OC-192 (STM-64) LR-2 pluggable XFP optic (LC connector). Range up to 80 km over SMF.

**Corporate Headquarters**

San Jose, CA USA  
T: +1-408-333-8000  
info@brocade.com

**European Headquarters**

Geneva, Switzerland  
T: +41-22-799-56-40  
emea-info@brocade.com

**Asia Pacific Headquarters**

Singapore  
T: +65-6538-4700  
apac-info@brocade.com

© 2010 Brocade Communications Systems, Inc. All Rights Reserved. 11/10 GA-DS-1344-01

Brocade, the B-wing symbol, BigIron, DCFM, DCX, Fabric OS, FastIron, IronView, NetIron, SAN Health, ServerIron, Turbolron, and Wingspan are registered trademarks, and Brocade Assurance, Brocade NET Health, Brocade One, Extraordinary Networks, MyBrocade, and VCS are trademarks of Brocade Communications Systems, Inc., in the United States and/or in other countries. Other brands, products, or service names mentioned are or may be trademarks or service marks of their respective owners.

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Brocade. Brocade reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This informational document describes features that may not be currently available. Contact a Brocade sales office for information on feature and product availability. Export of technical data contained in this document may require an export license from the United States government.

**BROCADE**